

MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME
Gulf States Asphalt Co., Inc.
P.O. Box 508 (or 300 Christy Place)
South Houston, TX 77597

EMERGENCY TELEPHONE NUMBER
(713) 941-4410

DATE OF PREPARATION
August 8, 1988

INFORMATION TELEPHONE NUMBER
(713) 941-4410

SECTION I -- PRODUCT IDENTIFICATION

Product No.	Product Name	Product Classification
P6001	Azrock	
and	Floor Tile Adhesive	Asphalt Cutback Mastic
P6005	Cutback Type 2	

SECTION II -- HAZARDOUS INGREDIENTS

INGREDIENT	CAS NO.	WEIGHT PCT. RANGE	FLAMMA- BILITY D.O.T.	OCCUPATIONAL EXPOSURE LIMITS TLV	VAPOR PRESSURE mm Hg, 70°F
Asphalt ¹	8052-42-4	40-55	---	5 mg/M ³	ACGIH ² Nil
Mineral Spirits	64741-41-9	20-25	Comb.	100ppm	ACGIH 2.0
Naphtholite 66/3	647-42- 48-9	10-14	Flam.	300ppm	ACGIH 12.0

¹The TLV for asphalt applies to asphalt in its vapor state, i.e., when it is heated. It is not applicable in the above product--not hazardous.

²ACGIH has dropped asphalt from its listing.

SECTION III -- PHYSICAL DATA

BOILING RANGE, °F: 200 - >900 % VOLATILES VOLUME: 39

VAPOR DENSITY: XX Heavier, Lighter THAN AIR

EVAPORATION RATE: Faster, XX Slower THAN ETHER

WEIGHT/GALLON, Range: 7.2 - 7.8 Lbs.

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION

OSHA Flammable

DOT Flammable

FLASH POINT, °F: 885 (Pensky-Martens)

LEL: 1 - 7

EXTINGUISHING MEDIA: XX Foam; XX "Alcohol" Foam; XX CO₂;
XX Dry Chemical; XX Water Fog; Other

UNUSUAL FIRE AND EXPLOSION HAZARDS

Do not use liquid water. This may cause the fire to spread.

SPECIAL FIREFIGHTING PROCEDURES

Treat as any hydrocarbon fire.

RESPIRATORY PROTECTION

If area can not be adequately ventilated, use self-contained breathing equipment. Maintain vapor levels below 60 ppm.

VENTILATION

Use forced air ventilation to maintain vapor below 60 ppm.

PROTECTIVE GLOVES

Not normally required unless skin is extremely sensitive.

EYE PROTECTION

Do not allow to splash in eyes; wear glasses or goggles if necessary.

OTHER PROTECTIVE EQUIPMENT

Not applicable

HYGIENIC PRACTICES

Wash hands well before eating. Change clothes at least daily. If large amounts spill onto clothes or skin, remove as soon as possible.

SECTION IX -- SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep away from sparks, open flames, or other sources of ignition.

Do not apply in an area where open flames or sparks are present. Use with adequate ventilation.

OTHER PRECAUTIONS

Keep away from children. Do not take internally.